

In order to properly size and quote a valve(s) for your job, please complete the following:

***Required fields**

* Is this for an order?

* Is this for pricing only?

- * 1) Piston diameter(s): _____ Single _____ Dual _____ Telescopic 1 - 2 - 3 stage
- * 2) Speed of the car (F.P.M.): _____ * Capacity of the car: _____
- * 3) No load pressure; "B" port reading static": (no load) _____ * **or** empty car weight: _____
- * 4) Is elevator roped 1:2: **Yes** **No** * Does this job require down speed regulation: _____
- * 5) Do you require an OSV (pipe rupture or seismic safety valve) for this installation? _____
- * 6) Quantity of valves required for job: _____
- 7) If replacing a Maxton valve the serial number is: _____

- **Coil voltage on valve:** 115VAC (RED) 230VAC (GREEN) 110VDC (BLACK)

*** COMPLETE FOR UC4/ UC4M /UC4MR:**
 - Facing the adjustments, jack is to the:

Left Right

- Type of flanges:	Pump	Jack	Tank
2" NPT (Thd)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2" Grooved	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Low Pressure Switch Yes No (CIRCLE ONE)

Quick Disconnect Coupling (1/8" NPT) Yes No

Quick Disconnect Nipples (1/8" NPT) Yes No

*** COMPLETE FOR UC1/UC1A/UC2/UC2A:**
 - The bottom port is the (circle one): PUMP / TANK Flanges:

Flanges:	2"	2.5"	3"	2"	2.5"
	<u>Grooved</u>	<u>Grooved</u>	<u>Grooved</u>	<u>NPT</u>	<u>NPT</u>
Pump:	<input type="checkbox"/>	<input type="checkbox"/>	+ <input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Jack:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Tank	<input type="checkbox"/>	<input type="checkbox"/>	++ <input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Low Pressure Switch Yes No (CIRCLE ONE)

Quick Disconnect Coupling (1/8" NPT) Yes No

Quick Disconnect Nipples (1/8" NPT) Yes No

+ Not recommended on UC2A
 ++ Not recommended on UC2

We also carry:

- MAXGLIDE OIL ADDITIVE (Eliminates stick slip / chatter)
- ISOLATION COUPLINGS (2", 2.5", 3" Grooved)
- TDF (Tank discharge filtration system)
- MAXVIEW OIL COMPARATER (Check for contamination)

SAFETACH ELEVATOR PERFORMANCE METER



Take advantage of our 30 day trial offer!!

Call for more information or visit www.safetach.com

Remember: You can order on-line or size valves on our website @ www.maxtonvalve.com 24 hrs a day, 7 days a week! For assistance contact Sales at (775) 782-1700

Your Name: _____ Your phone #: _____

Company Name: _____ Your fax #: _____

Bill To City Address: _____

Shipping Address: _____

PO# or Credit Card # _____ Name on credit card _____

Shipping Instructions: _____ (UPS ground service can take up to 6 business days depending on your location)



Maxton Manufacturing Company • 1728 Orbit Way • Minden, NV 89423-4114 • USA
 1-775-782-1700 • www.MaxtonValve.com

Fax 1-775-782-1701 • e-mail: info@MaxtonValve.com