

In order to properly size and quote a valve(s) for your job, please complete all fields:

☐ Is this for an order?

☐ Is this for pricing only?

If Replacing a Maxton Valve the Serial Number is: _____

Quantity of valves required for job: _____

If more than 1 is this for: ☐ Separate Elevators, ☐ Tandem/Dual Pump Units.

Information Required for Valve Sizing

Piston Info: (check applicable)

☐ Single or ☐ Dual, ☐ Roped (1:2), ☐ Multi Stage (Telescopic), Diameter(s) _____

Other Info:

Contract Speed _____ Capacity of Car _____

Empty Static Pressure "PSI"; "B" port reading: (no load) _____ or empty car weight: _____

Is Down Speed Regulation required? ☐ Yes ☐ No

Do you require an OSV (pipe rupture or seismic safety valve) for installation? _____

Coil Voltage (select one)

☐ 120 VAC

☐ 240 VAC

☐ 115 VDC

COMPLETE FOR UC4/ UC4M /UC4MR:

Facing the adjustments, jack is to the:

☐ Left ☐ Right

COMPLETE FOR UC1A/UC2A:

Type of Flanges:	Pump	Jack	Tank
2" NPT	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2.5" NPT	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2" Grooved	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2.5" Grooved	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
3" Grooved + not recommended for UC2A	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

COMPLETE FOR OSV:

Type of Flanges:	Jack	Tank
2" NPT	<input type="checkbox"/>	<input type="checkbox"/>
2.5" NPT	<input type="checkbox"/>	<input type="checkbox"/>
2" Grooved	<input type="checkbox"/>	<input type="checkbox"/>
2.5" Grooved	<input type="checkbox"/>	<input type="checkbox"/>
3" Grooved	<input type="checkbox"/>	<input type="checkbox"/>

<u>Optional Products:</u>	QTY	<u>Optional Products:</u>	Size	QTY
Low Pressure Switch (PSNO-2)		TDF1 (125 GPM) Tank Discharge Filter	<input type="checkbox"/> 2" NPT <input type="checkbox"/> 2" Grooved	
Quick Disconnect Coupling (1/8" NPT)		TDF2 (250 GPM) Tank Discharge Filter	<input type="checkbox"/> 2" NPT <input type="checkbox"/> 2" Grooved	
Quick Disconnect Nipples (1/8" NPT)		Isolation Coupling	<input type="checkbox"/> 2" NPT <input type="checkbox"/> 2" Grooved <input type="checkbox"/> 2.5" Grooved <input type="checkbox"/> 3" Grooved	
MAXGLIDE OIL ADDITIVE, 1 Gallon (Eliminates stick slip / chatter)		Shut Off Ball Valves	<input type="checkbox"/> 2" NPT <input type="checkbox"/> 2" Grooved <input type="checkbox"/> BV1-4A <input type="checkbox"/> 2.5" NPT <input type="checkbox"/> 2.5" Grooved <input type="checkbox"/> BV1-8A <input type="checkbox"/> 3" Grooved <input type="checkbox"/> BV3/4	
SafeTach2 Elevator Performance Meter				

**Remember: You can order on-line or size valves on our website @ www.maxtonvalve.com
24 hrs. a day, 7 days a week! For assistance contact Sales at (775) 782-1700**

Name: _____ Phone #: _____

Company Name: _____ Fax #: _____

Bill To City Address: _____

Shipping Address: _____

PO# or Credit Card # _____ Name on Credit Card: _____

Shipping Instructions: _____ Credit Card Expiration Date _____

(UPS ground service can take up to 6 business days depending on your location)

Certifications
Maxton is ISO 9001:2015 certified and
all main line products are CSAB44 and/or UL Listed.

