

In order to properly size and quote a valve(s) for your job, please complete the following:

***Required fields**

*** Is this for an order?**

*** Is this for pricing only?**

- * 1) Piston diameter(s): _____ Single _____ Dual _____ Telescopic 2 or 3 stage
- * 2) Speed of the car (F.P.M.): _____ * Capacity of the car: _____
- * 3) No load pressure; "B" port reading static: (no load) _____ * **or** empty car weight: _____
- * 4) Is elevator roped 1:2: **Yes** **No** * Does this job require down speed regulation: _____
- * 5) Do you require an OSV (pipe rupture or seismic safety valve) for this installation? _____
- * 6) Quantity of valves required for job: _____ If more than 1 is this for Separate Elevators.
 Tandem/Dual Pump Units.
- 7) If replacing a Maxton valve the serial number is: _____

* **Coil voltage on valve:** 115VAC (RED) 230VAC (GREEN) 115VDC (BLACK)

*** COMPLETE FOR UC4/ UC4M /UC4MR:**
- Facing the adjustments, jack is to the:

Left Right

- Type of flanges:	Pump	Jack	Tank
2" NPT (Thd)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2" Grooved	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Low Pressure Switch Yes No (CIRCLE ONE)

Quick Disconnect Coupling (1/8" NPT) Yes No

Quick Disconnect Nipples (1/8" NPT) Yes No

*** COMPLETE FOR UC1/UC1A/UC2/UC2A:**
-The bottom port is the (circle one): PUMP / TANK Flanges:

Flanges:	2"	2.5"	3"	2"	2.5"
	Grooved	Grooved	Grooved	NPT	NPT

Pump:	<input type="checkbox"/>	<input type="checkbox"/>	+ <input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Jack:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Tank:	<input type="checkbox"/>	<input type="checkbox"/>	++ <input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Low Pressure Switch Yes No (CIRCLE ONE)

Quick Disconnect Coupling (1/8" NPT) Yes No

Quick Disconnect Nipples (1/8" NPT) Yes No

+ Not recommended on UC2A
++ Not recommended on UC2

We Also Carry:

- MAXGLIDE OIL ADDITIVE (Eliminates stick slip / chatter)
- ISOLATION COUPLINGS (2", 2.5", 3" Grooved, 2" NPT)
- TDF (Tank discharge filtration system)
- MAXVIEW OIL VIEWING DEVICE (Check for contamination)
- SHUT OFF BALL VALVES (2", 2.5" Grooved or NPT)

SAFETACH ELEVATOR PERFORMANCE METER



Call for more information

**Remember: You can order on-line or size valves on our website @ www.maxtonvalve.com
24 hrs. a day, 7 days a week! For assistance contact Sales at (775) 782-1700**

Name: _____ Phone #: _____

Company Name: _____ Fax #: _____

Bill To City Address: _____

Shipping Address: _____

PO# or Credit Card # _____ Name on Credit Card: _____

Shipping Instructions: _____ (UPS ground service can take up to 6 business days depending on your location)

Certifications
Maxton is ISO 9001:2008 certified and
all main line products are CSAB44 and UL Listed.

