

*In order to properly size and quote a valve(s) for your job, please complete all **REQUIRED** fields:*

**\*Required fields**

**\* Is this for an order?**

**\* Is this for pricing only?**

- \* 1) Piston diameter(s): \_\_\_\_\_ Single \_\_\_\_\_ Dual \_\_\_\_\_ Telescopic 2 or 3 stage
- \* 2) Speed of the car (F.P.M.): \_\_\_\_\_ \* Capacity of the car: \_\_\_\_\_
- \* 3) Empty Static Pressure "PSI"; "B" port reading: (no load) \_\_\_\_\_ \* **or** empty car weight: \_\_\_\_\_
- \* 4) Is elevator roped 1:2:  **Yes**  **No** \* Does this job require down speed regulation: \_\_\_\_\_
- \* 5) Do you require an OSV (pipe rupture or seismic safety valve) for this installation? \_\_\_\_\_
- \* 6) Quantity of valves required for job: \_\_\_\_\_ If more than 1 is this for  Separate Elevators.  
 Tandem/Dual Pump Units.
- \* 7) If replacing a Maxton valve the serial number is: \_\_\_\_\_

**\* Coil voltage on valve:**  115VAC (RED)  230VAC (GREEN)  115VDC (BLACK)

**\* COMPLETE FOR UC4/ UC4M /UC4MR:**  
- Facing the adjustments, jack is to the:

Left  Right

|                    |                          |                          |                          |
|--------------------|--------------------------|--------------------------|--------------------------|
| - Type of flanges: | Pump                     | Jack                     | Tank                     |
| 2" NPT (Thd)       | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 2" Grooved         | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

Low Pressure Switch Yes No (CIRCLE ONE)

Quick Disconnect Coupling (1/8" NPT) Yes No

Quick Disconnect Nipples (1/8" NPT) Yes No

**\* COMPLETE FOR UC1A/UC2A:**  
-The bottom port is the (circle one): PUMP / TANK Flanges:

|          |         |         |         |     |      |
|----------|---------|---------|---------|-----|------|
| Flanges: | 2"      | 2.5"    | 3"      | 2"  | 2.5" |
|          | Grooved | Grooved | Grooved | NPT | NPT  |

|       |                          |                          |                             |                          |                          |
|-------|--------------------------|--------------------------|-----------------------------|--------------------------|--------------------------|
| Pump: | <input type="checkbox"/> | <input type="checkbox"/> | + <input type="checkbox"/>  | <input type="checkbox"/> | <input type="checkbox"/> |
| Jack: | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>    | <input type="checkbox"/> | <input type="checkbox"/> |
| Tank: | <input type="checkbox"/> | <input type="checkbox"/> | ++ <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

Low Pressure Switch Yes No (CIRCLE ONE)

Quick Disconnect Coupling (1/8" NPT) Yes No

Quick Disconnect Nipples (1/8" NPT) Yes No

+ Not recommended on UC2A  
++ Not recommended on UC2

*We Also Carry:*

- MAXGLIDE OIL ADDITIVE (Eliminates stick slip / chatter)
- ISOLATION COUPLINGS (2", 2.5", 3" Grooved, 2" NPT)
- TDF (Tank discharge filtration system)
- SHUT OFF BALL VALVES (2", 2.5" Grooved or NPT, 3" Grooved)

**SAFETACH2 ELEVATOR PERFORMANCE METER**



*Call for more information*

**Remember: You can order on-line or size valves on our website @ [www.maxtonvalve.com](http://www.maxtonvalve.com)**  
**24 hrs. a day, 7 days a week! For assistance contact Sales at (775) 782-1700**

Name: \_\_\_\_\_ Phone #: \_\_\_\_\_

Company Name: \_\_\_\_\_ Fax #: \_\_\_\_\_

Bill To City Address: \_\_\_\_\_

Shipping Address: \_\_\_\_\_

PO# or Credit Card # \_\_\_\_\_ Name on Credit Card: \_\_\_\_\_

Shipping Instructions: \_\_\_\_\_ Credit Card Expiration Date \_\_\_\_\_

(UPS ground service can take up to 6 business days depending on your location)

Certifications  
Maxton is ISO 9001:2015 certified and all main line products are CSAB44 and/or UL Listed.

