



## VALVE ORDERING

### New Valve Ordering Requirements

#### UC1A/UC2A

- 1) Job Specs – Complete spec sheet #1 - #7 or provide existing Maxton serial number \_\_\_\_\_
- 2) Flanges – Jack port – 2” or 2.5” threaded or grv / 3” grv \_\_\_\_\_  
 Tank port - 2” or 2.5” threaded or grv / 3” grv \_\_\_\_\_  
 Pump port - 2” or 2.5” threaded or grv / 3” grv \_\_\_\_\_  
 \* 3” grv flanges are available for an additional charge – the 3” grv flange is not recommended for the pump port on a UC2A or tank port on a UC2 \*\*
- 3) Coils – 120 vac / 115 vdc / 240 vac / 185 vac  
 \* 115 vdc and 240 vac are available for an additional charge \*

#### UC4/4M/4MR

- 1) Job Specs – Complete spec sheet #1 - #7 or provide existing Maxton serial number \_\_\_\_\_
- 2) Flanges - Pump port – 2” threaded or grv \_\_\_\_\_  
 Jack port – Thread to Grv Adaptor \_\_\_ Yes \_\_\_ No  
 Tank port - Thread to Grv Adaptor \_\_\_ Yes \_\_\_ No  
 \* The thread to grv adaptors are available for an additional charge \*
- 3) Coils – 120 vac / 115 vdc / 240 vac / 185 vac  
 \* 115 vdc and 240 vac are available for an additional charge \*

Branch Contact Name \_\_\_\_\_ City / State \_\_\_\_\_ / \_\_\_\_\_

PH: Office / Cell \_\_\_\_\_ / \_\_\_\_\_ Email: \_\_\_\_\_

### Valve Exchange Ordering Requirements

#### UC1/UC1A/UC2/UC2A

- 1) Serial number from existing Maxton \_\_\_\_\_  
 \***Serial number location** – Older valves – below the ‘A’ port stamped into the body  
Newer valves – Two small labels – one on top of valve body in front of down block and behind the up block
- 2) Flanges - Jack port – 2” or 2.5” threaded or grv / 3” grv \_\_\_\_\_  
 Tank port - 2” or 2.5” threaded or grv / 3” grv \_\_\_\_\_  
 Pump port - 2” or 2.5” threaded or grv / 3” grv \_\_\_\_\_
- 3) Coils – Not included – available for an additional charge

#### UC4/4M/4MR

- 1) Serial number from existing Maxton \_\_\_\_\_  
 \***Serial number location** – Older valves – Behind the jack outlet below LS adjustor stamped into the valve body  
Newer valves – Two small labels –  
 (B44) Tank side of the control plate and back of valve body

Flange – Pump port – 2” threaded or grv \_\_\_\_\_  
 Thd to Grv Adaptors for the Jack & Tank ports \_\_\_\_\_

- 2) Coils – Not included – available for an additional charge

Branch Contact Name \_\_\_\_\_ City / State \_\_\_\_\_ / \_\_\_\_\_

PH: Office / Cell \_\_\_\_\_ / \_\_\_\_\_ Email: \_\_\_\_\_